# 4' Purifier Axiom Class II C1 Biosafety Cabinet with 10" sash opening, UV Light, Service Fixture, Vacu-Pass Portal and Base Stand



View online: https://www.labconco.com/product/4-purifier-axiom-class-ii-c1-biosafety-cabinet-with-10-sash-opening-uy-8/8685



Catalog Number: 304411101

#### Overview

The Axiom is an R&D 100 Awards for Innovation Finalist

The Axiom Class II Type C1 maximizes safety and flexibility as the first biosafety cabinet that can be used in a recirculating Type A mode for standard microbiological work or can be connected to an exhaust system to function in Type B mode for handling hazardous chemicals. The unique design includes the Chem-Zone™, providing chemical safety with a large, clearly defined area within the enclosure, bringing peace of mind when handling chemicals. Other features that make the Axiom safe and easy to operate include its ergonomic Inclination™ Technology and the intuitive MyLogic™ Operating System.

## <u>VIEW THE BSC MANAGEMENT EBOOK</u> **or** <u>SEE OUR SUSTAINABILITY INITIATIVES</u>

Axiom Type C1 BSCs provide personnel, product and environmental protection by filtering hazardous particulates and aerosols and are suitable for work in all biosafety levels. These biosafety cabinets discharge HEPA filtered exhaust air directly back to the laboratory, or into an exhaust system through an included connection. Axiom models are available with base stands and/or an Accessory Package (UV light, service fixture(s) and Vacu-Pass™ Cord and Cable Portal) included.

## **Specifications**

• Weight: 835.0 lbs

• Weight metric: 378.8 kg

Dimensions: 54.3" w x 32.7" d x 64.2" h
Dimensions metric: 137.9 x 83.1 x 163.1 cm

• Electrical: 115V, 50/60 Hz, 12A

• Product Subcategory: Class II, Type C1

Biosafety Cabinets
• Nominal Width: 4'

Protection Type: Product and Personnel
 Nominal Sash Opening: 10" (25 cm)

• **Built In Options:** Cord, Cable & Tubing Portal, UV Light, Valves (Air, Vacuum, etc.)

Region: U.S. and CanadaBase Stand: Included

• Conformance: CAN/CSA C22.2, NSF 49, UL

61010

• Exhaust Volume: 387-480 CFM

• Lighting: LED, Ultraviolet

Power Cord & Plug: North America, 115V, 20A

• Service Fixtures: One

### For Product Assistance



<u>Franco Pasqualini</u> Sales Representative



Jon Buzard
Customer Service Representative



