



designed for scientists



## ETS-D5

/// Data Sheet

Electronic contact thermometer with three patented IKA operating modes.

- with optimised PID control
- RESET function
- incl. stainless steel sensor H 62

Ensures perfect temperature control in liquid mediums, without overshooting the set temperature, even in the case of quick heating. Automatic switch-off of the temperature control function of the connected magnetic stirrer after three



designed for scientists

minutes if the temperature probe is not immersed in the medium (Error 5).



designed for scientists

## Technical Data

Temperature measuring range min. (width H62 sensor) [°C]	-10
Temperature measuring range max. (width H62 sensor) [°C]	400
Temperature measurement resolution [K]	0.1
Accuracy of temperature measurement [K]	±0.2 + tolerance PT1000 (DIN IEC 751 Class A)
Set temperature resolution [K]	±0.1
Heat control accuracy of medium with sensor [K]	±0.5
Immersion depth max. [mm]	200
Permissible ON time [%]	100
Dimensions (W x H x D) [mm]	82 x 83 x 22
Weight [kg]	0.2
Permissible ambient temperature [°C]	0 - 60
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 54
DC Voltage [V=]	8 - 16
Current consumption [mA]	15